

AERO MOBILE PANEL

This equipment makes available to its user 7 types of Voltage in only one point, spread on various points of distribution.

Technical characteristics :

Voltage supply : 3x400V + N + T

Dimensions :

Length : 1300 mm

Width : 900 mm

Height : 1150 mm

Weight : 480 Kg

Maneuverability ensured by a handle, two rear wheels as well as two regular wheels with brakes (to block it when used).

Supplied with the power cord.



Photo non contractuelle

Protection against shocks ensured by 8 trapezoidal support.

The various cables can be wrapped around the handle when moving.

Distribution example on the AERO 2 model (code : 49A53002) :

Voltage type	Type of plug	Available plugs
400V 50Hz	32A 3P + N + T	2
400V 50Hz	16A 3P + N + T	2
230V 50 Hz	16A 1P + N + T	2
12V 50 Hz	10A 2P	1
208V 400 Hz	40A 3P + N aeronautics	1
120V 400 Hz	30A 2P + T	1
36V 400 Hz	16A 3P	1
28.5V DC	32A 2P	2
28.5V DC	63A 2P aeronautics	1

Equipment :

- General Push button « On/Off »
- » 400Hz & DC Push button « On/Off
- « EmergenCy stop »
- Various indicators: operational /faulty
- Protection ensured by circuit breaker and fuse

Characteristics of use :

Frequency	Voltage	Current	Power
400Hz	208V	40A	15 000 VA
400Hz	120V	30A	3 600 VA
400Hz	36V	16A	990 VA
50Hz	400V	63A	42 000 VA
50Hz	230V	32A	7 000 VA
50Hz	12V	10A	120 VA
DC	28,5Vcc	63A	1 700 VA



Photo non contractuelle

Warning :

The following voltages cannot be exceeded, in any case:

- 400Hz, 15 000 VA all Voltages combined.
- 50Hz, 42 000 VA all Voltages combined.
- 28.5Vcc, 1 700 VA.

It should be noted that the whole of the equipment cannot produce more than 42,000 VA all Voltages and all types of signal combined.

ELAUL scop

Z.I Nord – Rue Joseph Cugnot
Tél. : +33 (0)5.63.22.21.21

B.P 832
Fax : +33 (0)5.63.22.21.22

www.elaul.fr

82008 MONTAUBAN CEDEX
Email : elaul@wanadoo.fr